

TEKNİK ÖZELLİK


Arayüz	"Data" Input Port: 1 x RJ-45 STP "PoE (Data + Power)" Output Port: 1 x RJ-45 STP AC Input power socket: 1
LED Indicator	System: Power x 1 (Green) PoE Port: Active, PoE ready/In Use x 1 (Green)
Network Kablo	10Base-T: 2-Pair UTP Cat. 3, 4, 5, up to 100M (328ft) 100Base-TX: 2-Pair UTP Cat. 3, 4, 5, up to 100M (328ft) 1000Base-T: 2-Pair UTP Cat. 5, 5e, 6 up to 100M (328ft) EIA/TIA- 568 100-ohm STP (100m)
Data Hızı	10/100/1000Mbps
Ölçüler (W x D x H)	115 x 62.5 x 31 mm
Ağırlık	177g
Unit Output Voltage	DC 50-54V, 0.6A
Güç Gereksinimi	100-240V AC, 50/60Hz, 0.75A max
Güç Tüketimi	30 watts max.
Number of devices that can be powered	1
Çalışma Sıcaklığı	0 ~ 50 degrees C
Saklama Sıcaklığı	-10 ~ 70 degrees C
Çalışma Nem Oranı	5 ~ 95%, Relative Humidity, non-condensing
Saklama Nem Oranı	5 ~ 95%, Relative Humidity, non-condensing

Power over Ethernet

PoE Standart	IEEE 802.3at Power over Ethernet Plus / PSE
PoE Power Output	DC 53V/30 watts
PoE Power supply Type	Mid-Span
Power Pin Assignment	4/5(+), 7/8(-)

Standart Uygunluğu

Standart Uygunluğu	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T Gigabit Ethernet IEEE 802.3at High Power over Ethernet IEEE 802.3af Power over Ethernet
Yönetmelik Uygunluğu	FCC Part 15 Class B, CE


Serdal AYCIÇEK
Sıyaç İşleri Şefi